

# CERTIFICATE

Issued to:  
Applicant:  
**B.V. Twentsche Kabelfabriek**  
**Spinnerstraat 15**  
**7481 KJ Haaksbergen, The Netherlands**

Manufacturer/Licensee:  
**B.V. Twentsche Kabelfabriek**  
**Spinnerstraat 15**  
**7481 KJ Haaksbergen, The Netherlands**

Product(s) : connector  
Trade name(s) : TKF  
Type(s)/model(s) : POWER CLICK

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 60998-1:2004 and EN 60998-2-3:2004;
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 900420


DEKRA hereby grants the right to use the KEMA-KEUR certification mark.

The KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration of the KEMA-KEUR certification agreement and under the conditions of the KEMA-KEUR certification agreement.

This certificate is issued on: 9 january 2012 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 2132666.01

DEKRA Certification B.V.



drs. G.J. Zoetbrood  
Managing Director




F.S. Strikwerda  
Certification Manager

© Integral publication of this certificate is allowed

All testing, inspection, auditing and certification activities of the former KEMA Quality are an integral part of the DEKRA Certification Group.

ACCREDITED BY  
THE DUTCH COUNCIL  
FOR ACCREDITATION



**SPECIFICATION OF THE CERTIFIED PRODUCT****Product data**

product	:	connector
trade name(s)	:	TKF
type(s)	:	Power Click
material	:	thermoplastic material

**Additional information**

The Power Click connector can only be used together with one of the two flat cables made by B.V. Twentsche Kabelfabriek which contains 3 x 2,5 mm<sup>2</sup> conductors (10363 provided with KEMA-KEUR) and 4 x 2,5 mm<sup>2</sup> conductor (10362 provided with KEMA-KEUR) in case of 3 x 2,5 mm<sup>2</sup> cable one entrance of the connector will be closed by a blue wire dummy (100558)

**Product data - type Power Click**

rated voltage	:	250 V ac
current	:	16 A
connection	:	2,5 mm <sup>2</sup> flexible (multi core)
rated connection capacity	:	2,5 mm <sup>2</sup> flexible (multi core)
connectable conductors	:	2,5 mm <sup>2</sup> flexible (multi core)
number of poles	:	3 or 4 poles
IP Class	:	IP40
reusability	:	Non reusable
cable	:	for cable with a diameter of 24,2 mm x 4,05 mm (4 wires) 17,9 mm x 4,05 mm (3 wires)
description	:	Power Click cable connection box, built-in, 4 times insulation piercing clamping units, 2 piercing terminals per pole on each side

**TESTS****Test requirements**

EN 60998-1:2004  
EN 60998-2-3:2004

**Test result**

The test results are laid down in DEKRA test file 2132666.01.

**Conclusion**

The examination proved that all test requirements were met.

Tested by : W.C. van Ginkel

Checked by : H.G.M. Kormelink

**Factory locations**

B.V. Twentsche Kabelfabriek  
Spinnerstraat 15, 7481 KJ,  
Haaksbergen The Netherlands